



## Standards



TYPE 5  
13982-1



TYPE 6  
13034



EN  
1073-2



EN  
1073-2


## Technical specifications



Self-adhesive zip flap for increased protection



Hood 3 pans allows much greater freedom of movement



Elasticated waistband for a perfect fit



Bat-wing sleeve allows much greater freedom of movement




- Taped seam flat for optimal sealing to asbestos fibers
- Elasticated waist for a better fit
- Special asbestos packaging for tracking
- Designed for maximum comfort with ultra-breathable material
- Its specific features allow freedom of movement
- NEW : also available with integrated overboots

# Material and seams


## SMS MATERIAL

Provide high breathability and optimum comfort



## TAPED SEAM

Internal stitching which is overtaped to offer increased strength and an effective barrier to liquids and micro and dangerous particules



## Applications

- Asbestos removal and abatement
- Asbestos sample
- Asbestos diagnostics
- Sanding work
- Fiberglass, resin and ceramic applications
- Installation of insulation work mineral wool

## Technical Data

Penetration of liquids resistance

Chemical properties of the fabric	Test method	Penetration	Repulsion
H <sub>2</sub> SO <sub>4</sub> - Sulphuric acid 30%	EN 368	Class 3	Class 3
NaOH - Sodium hydroxide 10%	EN 368	Class 3	Class 3
O Xylene	EN 368	0	0
Butan-1ol	EN 368	0	0

## Tests Results EN 13935-2

Seams strength

Test method	Results	Class
Seams strength – ISO 13935-2	78N	3/6

## Reference

L	XL	XXL	XXXL
WL-C1-03	WL-C1-04	WL-C1-05	WL-C1-06

**WL-C1-0X**



SMS SERIES

Units per carton : 50

Reference : WL-C1-0X